

## MILLING MACHINE

Manufacturer:	CORREANAYAK
Model:	PERFORMER - MG
Type:	Bed-Type with rotary table



## EQUIPMENT

STANDARD EQUIPMENT	OPTIONS
<ul style="list-style-type: none"> <li>• CNC Heidenhain</li> <li>• 2,5° Auto index milling head</li> <li>• Portable handwheel Heidenhain HR-410</li> <li>• Ethernet Board</li> <li>• Work Light</li> <li>• Linear ways X, Y, Z axes</li> <li>• Dynamic digital direct drives for all the axis</li> <li>• A, C type servo-motors</li> <li>• Hydraulic counterbalance on the vertical axis</li> <li>• Coolant equipment</li> <li>• EU Guarding</li> </ul>	<ul style="list-style-type: none"> <li>• Other CNC's</li> <li>• Electrospindle (15.000 – 24.000 rpm)</li> <li>• 20, 30, 40, 60 –post automatic tool changer</li> <li>• Chips removal equipment</li> <li>• Measurement and presetting touch probes</li> <li>• Coolant through the spindle (high pressure)</li> <li>• Full enclosed guarding</li> <li>• A/C electrical cabinet</li> <li>• MQL outer tool microlubrication system</li> </ul>

## TECHNICAL FEATURES

			<i>PERFORMER-MG</i>	
			<i>PERFORMER-2.000-MG</i>	<i>PERFORMER-3.000-MG</i>
<i>Table</i>	Surface	mm	1.400 x 1.250	
	Max. load table	kg	7.000	
<i>Traverses</i>	Longitudinal	mm	2.000	3.000
	Cross	mm	1.000 / 1.200	
	Vertical	mm	1.100	
<i>Feeds</i>	Rapid traverses x-y-z	m/min	20 - 30	
<i>Spindle</i>	Spindle nose		ISO - 50	
	Programmable speed	r.p.m.	3.000 / 6.000	
	Maximum power	kw	30	
	Maximum torque	Nm	764 / 1.300	
<i>Weight</i>	Machine weight	Kg	15.000	18.000